


# Spila round 600-15-830 1200LM switch / Socket



## Technical Details:

Luminous Flux:	1200 lm
LED Output:	14 W
Light Yield:	80 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	133 °
Unified Glare Rating (UGR):	<22
LED-Chip:	SMD 2835
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	15 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>15.000
Ambient Temperature (TA):	-10°C - 40°C

Dimensions:	680x65x53 mm
Mounting:	Wand
Montageart:	surface mounted
IP Class:	44
IK Code:	04
Housing Color	white
Housing Material:	plastic
Special Feature of Housing:	with switch/outlet
Cover:	opal
Net Weight:	635 g
Type of Packaging:	box
Dimensions of Packaging:	700x65x75
Weight incl. Packaging:	0.754 kg
Content Master Package:	10
Dimensions of Master Package:	725x350x175 mm
Weight Master Package:	7,62 kg
Product Line:	ECO Line
Warranty	3 years
Operating Hours:	30.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405114090
Certifications	CE,D
Barcode:	4250557808970

Information and Downloads:

