
LITEGEAR LED Lighting Solutions

Mean Well HLG-100H-24A





Product information "Mean Well HLG-100H-24A"

LED Power Supply

Mean Well HLG-A Series Single Output LED Switching Power Supply features universal AC input up to 264VAC, protections for short circuit, overload, over voltage, and over temperature, built-in active PFC function, and OCP point adjustments through the output cable or internal potentiometer. The Mean Well HLG-A Series is IP65 designed for indoor or outdoor installations for LED lighting and moving sign applications.

Product Features:

• usable for all DC 24V single-colour LED strips and LED bulbs

Technical Details:

• Mains input: AC 90 - 264V, 47 - 63Hz

Housing: AluminiumOutput voltage: DC 24V,

• Output voltage range: yes (DC 22 - 27V)

Rated power: 4AOutput power: 96WDimmable: no

• Protection: short circuit, over load, over voltage

• Scope: LED strips and Illumination

• IP class: IP67 for indoor and outdoor use

• Safety standars: F, SELV, TÜV, CE

Power Faktor: >0,95Efficiency: 93,5%

Ambient temperature: -20° to 70°C

Warranty: 5 years

Dimensions: 228 x 68 x 38,8 mm

Weight: 1,12 kg

Technical Details:

Power Consumption:	96 W
Power Factor (PF):	0.95
Operating Hours:	>62.000 h
Ambient Temperature (TA):	-20°C - 70°C
Housing Material:	aluminum
Housing Color	silver
Dimensions	220x68x39 mm
Net Weight:	1120 g
Warranty	5 years

Information and Downloads:

