


Mean Well HLG-40H-12A



Product information "Mean Well HLG-40H-12A"

LED Power Supply

Mean Well HLG-A Series Single Output LED Switching Power Supply features universal AC input up to 264VAC, protections for short circuit, overload, over voltage, and over temperature, built-in active PFC function, and OCP point adjustments through the output cable or internal potentiometer. The Mean Well HLG-A Series is IP67 designed for indoor or outdoor installations for LED lighting and moving sign applications.

Product Features:

- usable for all DC 12V single-colour LED strips and LED bulbs

Technical Details:

- Mains input: AC 90 - 305V, 47 - 63Hz
- Housing: Aluminium
- Output voltage: DC 12V
- Output voltage range: yes (DC 10,8 - 13,5V)
- Rated power: 3,33A
- Output power: 40W
- Dimmable: no
- Protection: short circuit, over load, over voltage
- Scope: LED strips and Illumination
- IP class: IP67 for indoor and outdoor use
- Safety standars: F, SELV, TÜV, CE
- Power Faktor: >0,98
- Efficiency: 86,5%
- Ambient temperature: -20° to 70°C
- Warranty: 5 years

Dimensions: 171 x 61,5 x 36,8 mm

Weight: 0,693 kg

Technical Details:

Power Consumption:	40 W
Power Factor (PF):	0.95
Operating Hours:	>62.000 h
Switching Cycles:	>100.000
Ambient Temperature (TA):	-20°C - 70°C
Housing Material:	aluminum
Housing Color	silver
Coating:	anodised
Dimensions	171x62x37 mm
Net Weight:	730 g
Warranty	5 years

Information and Downloads:

