



Tridonic Driver LCU 60W 24V IP67 TOP



Product information "Tridonic Driver LCU 60W 24V IP67 TOP"

TRI LCU60W 24V Top

Product description

- Nominal life-time of 50,000 h (at max ta 50 °C with a failure rate ≤ 0.2 % per 1,000 h)
- 24 V DC output voltage
- Cable
- Output power 60 W
- Type of protection IP67

Properties

- Casing: Aluminium, white
- Compact dimensions
- Overload protection
- Short-circuit protection
- No-load protection

Technical Data

- Rated supply voltage: 220 - 240 V
- Input voltage AC: 120 - 277 V
- Mains frequency: 50 / 60 Hz
- Power factor: 0.95
- Power factor at min. load (1): 0.75C
- Ambient temperature ta: -40 ... +60 °C
- Ambient temperature ta: (at life-time 50,000 h) 50 °C
- Max. casing temperature tc: 85 °C
- Dimensions L x W x H :240 x 40 x 21 mm

Technical Details:

Power Consumption:	60 W
Power Factor (PF):	0.95
Operating Hours:	>50.000 h
Ambient Temperature (TA):	-40°C - 60°C
Housing Material:	metal
Housing Color	silver
Dimensions	240x40x21 mm
Warranty	5 years

Information and Downloads:

