



# Fenestra Value Rectangle MKII 6030 36-830-3600LM



## Technical Details:

Luminous Flux:	3600 lm
LED Output:	34 W
Light Yield:	100 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	110 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	36 W
Contains Driver:	✓
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 30 - 40V, 900mA
CC/CV:	CC+CV
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	595x295x13 mm
Mounting:	ceiling,wall
Montageart:	recessed
IP Class:	20
IK Code:	06
Housing Color	greywhite
Housing Material:	aluminum
Coating:	lacquered
Cover:	opal
Net Weight:	2047 g
Type of Packaging:	box
Dimensions of Packaging:	620x40x370
Weight incl. Packaging:	2.368 kg
Content Master Package:	4
Dimensions of Master Package:	640x190x395 mm
Weight Master Package:	10,41 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE,TÜV,ENEC,LM80,D
Barcode:	4250557809885

Information and Downloads:



