

# Retrova 1220 36-860-5150LM



## Technical Details:

Luminous Flux:	5150 lm
LED Output:	38 W
Light Yield:	137 lm/W
Light Temperature:	5800 K
Light Color:	cold white
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 2835
Number of LED:	176
Ignition Time:	<0,5 s
Input Current:	AC 198 - 264V, 50/60Hz, DC 176 - 276V
Power Consumption:	38 W
Contains Driver:	✓
Driver Manufacturer:	Osram
Power Factor (PF):	>0.97
Input Driver:	terminal
Output of Driver:	DC 27 - 54V, 500, 600, 650, 700mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	1228x100x82 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
IK Code:	10
Housing Color	grey
Housing Material:	PC
Special Feature of Housing:	shockproof
Cover:	prismatic
Net Weight:	1590 g
Type of Packaging:	box
Dimensions of Packaging:	1230x110x90
Weight incl. Packaging:	1.9 kg
Content Master Package:	4
Dimensions of Master Package:	1255x190x225 mm
Weight Master Package:	8,1 kg
Product Line:	ECO Line
Warranty	3 years
Operating Hours:	50.000 h L70/B30
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,D
Barcode:	4250557810430
Osram LED Treiber mit einstellbarem Ausgangsstrom:	
OT-Fit36: Leistung einstellbar:	25, 30,33,35W
EVG: ENEC-10/VDE EMC/EL/CE; geeignet für Notstrom	
Anzahl pro Automat:	10A: 20, 16A: 32 Stück

Information and Downloads:

