



Movara MKII 70/38-927-3230LM BL



Technical Details:

Luminous Flux:	3230 lm
LED Output:	37 W
Light Yield:	85 lm/W
Light Temperature:	2700 K
Light Color:	warmwhite
Color Rendering Index:	≥90 Ra
Color Consistency (SDCM):	<3
Beam Angle:	90x60 °
Unified Glare Rating (UGR):	<6
Light Emission:	
LED-Chip Manufacturer:	Luminus
LED-Chip:	COB
Number of LED:	1
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	38 W
Contains Driver:	✓
Driver Manufacturer:	Osram
Power Factor (PF):	>0.98
Input Driver:	lighting track
Output of Driver:	DC 33-42V, 1050mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Power rail
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-10°C - 40°C

Dimensions:	193x70x169 mm
Mounting:	Decke
Montageart:	surface mounted
Pivot Range pan:	355 °
Pivot Range tilt:	90 °
IP Class:	20
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	3-Phase Track Adapter
Cover:	Lens
Net Weight:	900 g
Type of Packaging:	box
Dimensions of Packaging:	196*75*175
Weight incl. Packaging:	0.95 kg
Content Master Package:	16
Dimensions of Master Package:	410*320*370 mm
Weight Master Package:	16 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	35.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,LM80
Barcode:	4250557813851
Wallwasher Tracklight	
für Werbebanner oder Verkaufsregale	
for banners or shelves	
Anzahl/Qty. 16A fuse: 25 pcs.	
Strom einstellbar: 800/900/950/1050mA 29-38W	

Information and Downloads:

