


Instatube Advance 1200 20-840-2480LM



Technical Details:

Luminous Flux:	2480 lm
LED Output:	20 W
Light Yield:	124 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥85 Ra
Color Consistency (SDCM):	<5
Beam Angle:	130 °
Light Emission:	downward
LED-Chip Manufacturer:	Samsung
LED-Chip:	SMD 5630
Ignition Time:	<1 s
Input Current:	AC 100 - 240V, 50/60Hz, DC 180-230V
Power Consumption:	20 W
Contains Driver:	✓
Power Factor (PF):	>0.9
CC/CV:	CC
Input Lamp:	cable with flying leads
Switching Cycles:	>50.000
Ambient Temperature (TA):	-20°C - 50°C
Storage Temperature:	-40°C - 60°C

Dimensions:	1200x32x43 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
IK Code:	08
Housing Color	silver
Housing Material:	aluminum
Cover:	frosted
Net Weight:	710 g
Type of Packaging:	box
Dimensions of Packaging:	1310x38x48
Weight incl. Packaging:	0.82 kg
Content Master Package:	15
Dimensions of Master Package:	1340x210x160 mm
Weight Master Package:	14,2 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE,D
Barcode:	4250557810614
Inkl. Montage Clips, Klebepads und Einspeiser	

Information and Downloads:

