


Lipal Sockellicht 3-830-48LM AZ



Technical Details:

Luminous Flux:	48 lm
LED Output:	2 W
Light Yield:	16 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥84 Ra
Color Consistency (SDCM):	<4
Beam Angle:	83 °
Light Emission:	
LED-Chip Manufacturer:	Cree
LED-Chip:	High-Power
Number of LED:	1
Ignition Time:	<1 s
Input Current:	AC 100 - 240V, 50/60Hz
Power Consumption:	3 W
Contains Driver:	✓
Driver Manufacturer:	Eagle Rise
Power Factor (PF):	>0.5
Input Driver:	cable with flying leads
Output of Driver:	DC 2,5-4V, 700mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>25.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	80x80x90 mm
Installation Depth:	56 mm
Cut-Out Dimensions:	65,5x65,5 mm
Mounting:	Wand
Montageart:	recessed
IP Class:	65
Housing Color	grey
Housing Material:	aluminum
Coating:	powder-coated
Cover:	clear
Net Weight:	256 g
Type of Packaging:	box
Dimensions of Packaging:	105x90x90
Weight incl. Packaging:	0.284 kg
Content Master Package:	50
Dimensions of Master Package:	470x200x400 mm
Weight Master Package:	14,94 kg
Product Line:	ECO Line
Warranty	2 years
Operating Hours:	30.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,LM80,D
Barcode:	4250557810713

Information and Downloads:



