


Nava Circle 200 18-CCT SELECT-1620LM



Technical Details:

Luminous Flux:	1620 lm
LED Output:	16 W
Light Yield:	90 lm/W
Light Temperature:	3000,4000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Unified Glare Rating (UGR):	<24
Light Emission:	downward
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	18 W
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.9
Input Driver:	cable with flying leads
Output of Driver:	DC 27 - 42V, 600mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-10°C - 40°C

Dimensions:	200x45 mm
Installation Depth:	27 mm
Cut-Out Dimensions:	165 mm
Mounting:	ceiling,wall
Montageart:	recessed
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Special Feature of Housing:	beleuchteter Glasrand
Cover:	Glas gefrostet
Net Weight:	650 g
Type of Packaging:	box
Dimensions of Packaging:	243x70x225
Weight incl. Packaging:	0.781 kg
Content Master Package:	8
Dimensions of Master Package:	320x260x460 mm
Weight Master Package:	6,8 kg
Product Line:	ECO Line
Warranty	3 years
Operating Hours:	30.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,D
Barcode:	4250557812366
Wahl der Lichtfarbe zw. 3000/4000 Kelvin	
CCT select: 3000/4000 Kelvin	

Information and Downloads:



