


Alwetra 500E Battery Emergency Modul IP65/IK10-650lm



Technical Details:

Luminous Flux:	650 lm
LED Output:	5 W
Light Yield:	130 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD
Ignition Time:	<1 s
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	5 W
Contains Driver:	✓
Input Lamp:	plug connector
Switching Cycles:	>25.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-10°C - 40°C
Storage Temperature:	-10°C - 40°C

Dimensions:	510x86x67 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	65
IK Code:	10
Housing Color	white
Housing Material:	Aluminium+PC
Special Feature of Housing:	polycarbonate
Cover:	frosted
Net Weight:	1250 g
Type of Packaging:	box
Weight incl. Packaging:	1.25 kg
Product Line:	Advance Line
Warranty	2 years
Operating Hours:	25.000 h
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE,D
Barcode:	4250557818160
Batteriebetrieb:	min. 3h
Ladestrom	5-7W
Batterie:	Lithium / 0,35KG /

Information and Downloads:

