

Newtura Round 240-20-830/840-1700LM CCT select



Product information "Newtura Round 240-20-830/840-1700LM CCT select"

Ceiling light with CCT select

Newtura is a round surface-mounted luminaire with an integrated LED driver. Via an integrated switch the installer can select 3 different light colors: 3000, 3500, 4000 Kelvin (warm white to natural white). Optionally also available as a dimmable version (Dali or 0-10V). Easy assembly thanks to separate mounting plate and twist lock with additional fall protection using a safety rope. Integrated electrical terminal block for power loop. Can also be suspended using a rope set. On request, the lamp can also be equipped with an internal microwave sensor or battery emergency light pack. As a dimmable variant with Meanwell® LC-45 driver, it is also suitable for operation on emergency power central battery systems in accordance with EN 60598-2-22. Due to the large internal space, emergency switch relays can also be integrated.

High quality Samsung LED chips for long life and high luminous flux maintenance. Elegant and high-quality die-cast aluminum housing. Universal mounting options.

Technical Details:

Luminous Flux	1700 lm
Light Yield:	85 lm/W
Light Temperature:	3000,3500,4000 K
Color Rendering Index (CRI)	≥82 Ra
Color Consistency (SDCM):	4
Power Consumption:	20 W
Power Factor (PF):	0.95
Operating Hours:	>50.000 h L80/B20
Switching Cycles:	>100.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-20°C - 40°C
Housing Material:	aluminum
Housing Color	white
Coating:	powder-coated
Dimensions	240x35 mm
Net Weight:	1185 g
Warranty	5 years

Information and Downloads:

