

# Modulux Linear LED- Modul 60-14/20-830-3000lm-WH



## Technical Details:

Luminous Flux:	3000 lm
LED Output:	19 W
Light Yield:	150 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 150mA, 50/60Hz
Power Consumption:	20 W
Contains Driver:	✓
Power Factor (PF):	>0.95
Input Driver:	lighting track
Output of Driver:	DC 55-80V, 280mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Power rail
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-25°C - 60°C
Storage Temperature:	-40°C - 85°C

Dimensions:	600x60x11 mm
Mounting:	Decke
IP Class:	20
IK Code:	03
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	3-Phase adapter
Cover:	Lens
Net Weight:	550 g
Type of Packaging:	none
Weight incl. Packaging:	0.55 kg
Content Master Package:	10
Dimensions of Master Package:	670x350x240 mm
Weight Master Package:	7,8 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,TÜV,D
Barcode:	4250557819969
spezielle Optik für Supermarktregale	
special optics for shelf lighting in supermarkets	
2 x 30° double asymmetric	
Power adjust: 14/16/18/20W 2050-2900LM max.	

Information and Downloads:



