


Alvera Line MKII 1500 60-840-8400LM DALI Dim



Technical Details:

Luminous Flux:	8400 lm
LED Output:	58 W
Light Yield:	140 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI
LED-Chip Manufacturer:	Epistar
LED-Chip:	SMD 2835
Number of LED:	325
Ignition Time:	<0,5 s
Input Current:	AC 180-264 max.V, 50Hz
Power Consumption:	60 W
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 27-40V, 1400mA
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>50.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-20°C - 60°C
Storage Temperature:	-40°C - 55°C

Dimensions:	1525x85x78 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
IK Code:	10
Housing Color	white
Housing Material:	aluminum
Special Feature of Housing:	opt. Polycarbonat Cover
Cover:	opal
Net Weight:	2600 g
Type of Packaging:	box
Dimensions of Packaging:	160x92x82
Weight incl. Packaging:	2.88 kg
Content Master Package:	4
Dimensions of Master Package:	1620x190x220 mm
Weight Master Package:	14 kg
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE,LM80,D
Barcode:	4250557821283
Einfache, und schnelle Montage, In/Out Terminal	
Schnellverschluß Endkappen	
Dali dimmbar, Durchgangsverdrahtung	
5 wire Terminal for loop, Dali dim	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

