


Fenestra OFFICE Rectangle MKII 12040 36-830-4000LM



Technical Details:

Luminous Flux:	4000 lm
LED Output:	36 W
Light Yield:	111 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip:	SMD 4014
Number of LED:	192
Ignition Time:	<0,5 s
Input Current:	AC 220-240VV, 50/60Hz
Power Consumption:	36 W
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 30 - 42V, 900mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	1195x395x10 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20
IK Code:	03
Housing Color	white
Housing Color (RAL Code):	similar 9003
Housing Material:	aluminum
Coating:	lacquered
Cover:	prismatic
Net Weight:	4200 g
Type of Packaging:	box
Dimensions of Packaging:	1220x370x40
Content Master Package:	6
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,TÜV,GS,ENEC,D
Barcode:	4250557821955
Geeignet für Bildschirmarbeitsplätze UGR <19	
PMMA LGP light guide plate	
PS Prismatic Diffusor	

Information and Downloads:

