


Arbora Slim 80-830/860-10400LM



Technical Details:

Luminous Flux:	10400 lm
LED Output:	80 W
Light Yield:	130 lm/W
Light Color:	variable 3000-6000K
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120x50 °
Unified Glare Rating (UGR):	<6
Light Emission:	
Dimmable:	✓
Method of Dimming:	Push-Dim
LED-Chip:	SMD 2835
Number of LED:	528
Ignition Time:	<0,5 s
Input Current:	AC 100- 240V, 50/60Hz
Power Consumption:	80 W
Contains Driver:	✓
Power Factor (PF):	>0.95
Input Driver:	cable with plug
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-20°C - 50°C

Dimensions:	1065x225x1950 mm
Mounting:	ground
IP Class:	20
IK Code:	06
Housing Color	silver
Housing Color (RAL Code):	similar 9006
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	Steel base
Cover:	Reflector
Net Weight:	11300 g
Type of Packaging:	box
Weight incl. Packaging:	13.6 kg
Content Master Package:	1
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE
Barcode:	4250557812014
Lichtaustritt 55W/120° oben und 25W/25° unten	
inkl. Präsenz- und Helligkeitssensor, Push Dimmer	
Light distribution up/down: 55W/120° and 25W/50°	
inkl. occupancy detector and brightness detection	
separ. Push dimmer for up/down, CCT adjust	

Information and Downloads:

