

SOLVELA BRICK 6-730-900LM IP65



Technical Details:

| | |
|---------------------------|--------------------|
| Luminous Flux: | 900 lm |
| LED Output: | 6 W |
| Light Yield: | 150 lm/W |
| Light Temperature: | 3000 K |
| Light Color: | warmwhite |
| Color Rendering Index: | ≥80 Ra |
| Color Consistency (SDCM): | <5 |
| Beam Angle: | 140x70 ° |
| Light Emission: | downward |
| LED-Chip: | SMD 2835 |
| Ignition Time: | <1 s |
| Input Current: | DC 3,7V, 3000mA mA |
| Power Consumption: | 6 W |
| CC/CV: | CV |
| Switching Cycles: | >15.000 |
| Ambient Temperature (TA): | -10°C - 45°C |
| Storage Temperature: | 0°C - 50°C |

| | |
|--|-----------------------|
| Dimensions: | 228x95x43 mm |
| Mounting: | Wand |
| Montageart: | surface mounted |
| IP Class: | 65 |
| Housing Color | white |
| Housing Material: | ABS+PC, Alu Anti UV |
| Special Feature of Housing: | Sensor 6m /Solarpanel |
| Cover: | Lens |
| Net Weight: | 548 g |
| Type of Packaging: | box |
| Weight incl. Packaging: | 0.658 kg |
| Content Master Package: | 24 |
| Dimensions of Master Package: | 490x320x223 mm |
| Weight Master Package: | 15,18 kg |
| Product Line: | ECO Line |
| Warranty | 2 years |
| Operating Hours: | 15.000 h L80/B20 |
| Disposal Obligation: | ✓ |
| Customs Tariff Number: | 9405413990 |
| Certifications | CE |
| Barcode: | 4250557822426 |
| Solarleuchte für Wandmontage, modernes Design | |
| solar wall pack light stylish design, 2 work modes | |
| integrierter Bewegungssensor mit Dimmung/Standby | |
| integrated motion sensor 120° <6m | |
| replaceable battery pack | |

Information and Downloads:

