


CIELLA LED-Unit 27-830/840-WH 3730lm



Technical Details:

Luminous Flux:	3730 lm
Light Yield:	124 lm/W
Light Color:	dualwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD
Ignition Time:	<0,5 s
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	30 W
Contains Driver:	✓
Driver Manufacturer:	KGP
Power Factor (PF):	>0.95
Input Driver:	Kabel mit Terminal
Output of Driver:	DC 30 - 42V, 350-700mA
CC/CV:	CC
Input Lamp:	cable with plug
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-40°C - 60°C

Dimensions:	148x99 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20 (44 room side)
IK Code:	08
Housing Color	black/white
Housing Material:	aluminum
Coating:	lacquered
Net Weight:	789 g
Type of Packaging:	box
Dimensions of Packaging:	177x152x142
Weight incl. Packaging:	0.886 kg
Content Master Package:	20
Dimensions of Master Package:	780x200x590 mm
Weight Master Package:	18 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	70.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,D
Barcode:	4250557824093
CCT Select:	3000, 3500, 4000K
Power Select:	15-30W, max. 3650lm >120lm/W
elektr. Anschlußdose für Durchgangsverdrahtung	
modulare Bauweise, kombinierbar mit Deckenringen	

Information and Downloads:

