

# LAREDA GU10 Pendant Spot



## Technical Details:

|                           |              |
|---------------------------|--------------|
| Light Emission:           | downward     |
| Input Lamp:               | terminal     |
| Ambient Temperature (TA): | -20°C - 50°C |
| Storage Temperature:      | -40°C - 60°C |

Information and Downloads:



|                                                 |                     |
|-------------------------------------------------|---------------------|
| Dimensions:                                     | 55x180 mm           |
| Mounting:                                       | Decke               |
| Montageart:                                     | surface mounted     |
| IP Class:                                       | 20                  |
| Housing Color                                   | white/black         |
| Housing Material:                               | aluminum            |
| Special Feature of Housing:                     | GU 10 Socket/Socket |
| Net Weight:                                     | 361 g               |
| Type of Packaging:                              | box                 |
| Weight incl. Packaging:                         | 0.423 kg            |
| Content Master Package:                         | 35                  |
| Dimensions of Master Package:                   | 557x404x297 mm      |
| Weight Master Package:                          | 15,06 kg            |
| Product Line:                                   | Advance Line        |
| Warranty                                        | 5 years             |
| Disposal Obligation:                            | ✓                   |
| Customs Tariff Number:                          | 8536619090          |
| Certifications                                  | CE                  |
| Barcode:                                        | 4250557822907       |
| Ideal für Wohnräume und Büros                   |                     |
| Perfect for residential applications and office |                     |
| Geringe Blendung und gerichtetes Licht          |                     |
| Low glare rate and concentrated light beams     |                     |
| 150cm cable/Kabel                               |                     |