

# Lifud LF-GMR075YV024A CV Power supply Flicker free



**Lifud**  
LED Driver



## Product information "Lifud LF-GMR075YV024A CV Power supply Flicker free"

### LED Power Supply

The Lifud LF-GMR075YV024A is an extremely versatile power supply for all kinds of passive LED projectors and strips. You can use it indoor installations such as cove lighting or inside linear luminaires.

### Product Features:

- usable for all DC 24V single-colour LED strips and LED bulbs

### Technical Details:

- Mains input: AC 220 - 240V, 47 - 63Hz (max. 200 - 264V AC)
- Housing: steel with plastic covers
- Output voltage: DC 24V +/-0,5V, constant voltage
- Rated power: 3,125A
- Output power: 75W
- Dimmable: no
- Protection: short circuit, over load, over voltage
- Scope: LED strips and Illumination
- Safety standars: SELV, TÜV, CE, CB
- Power Faktor: >0,95
- Efficiency: 88,5%

### Technical Details:

|                           |              |
|---------------------------|--------------|
| Power Consumption:        | 75 W         |
| Power Factor (PF):        | 0.95         |
| Switching Cycles:         | >100.000     |
| Ignition Time:            | <0,5 s       |
| Ambient Temperature (TA): | -30°C - 50°C |
| Housing Material:         | steel        |
| Housing Color             | Alu/blue     |
| Coating:                  | verzinkt     |
| Dimensions                | 285x30x21 mm |
| Net Weight:               | 265 g        |
| Warranty                  | 5 years      |

### Information and Downloads:

