

# Lifud ADD040-1050-42 Dali-2



## Product information "Lifud ADD040-1050-42 Dali-2"

### Dali 2 LED Power Supply

Constant current DC output LED driver with multi level selectable output current by dip switch. DALI- interface and push dim dimming. high efficiency up to 87%, with the fanless design for LED indoor lighting

Applications: LED office lighting, LED architectural lighting, LED panel and downlighting

### Product Features:

- Constant Current mode output with multiple levels selectable by dip switch
- Plastic housing with class II design
- Built-in active PFC function
- Standby power consumption < 0.7W
- Functions: DALI interface, push dimming
- power select output: 700-1050mA 25-40W
- dimming range: 1-100%
- Inrush Current < 25A&200uS
- Load Quantities of
- Circuit Breaker: Model B10 C10 B16 C16
- Quantity (pcs)            23 38 37 61

## Technical Details:

Power Consumption:	40 W
Power Factor (PF):	0.97
Operating Hours:	>50.000 h TC<80°C
Switching Cycles:	>100.000
Ambient Temperature (TA):	-20°C - 45°C
Housing Material:	plastic
Housing Color	white
Dimensions	145x46x27,5 mm
Net Weight:	0.123 g
Warranty	5 years

### Information and Downloads:

