

PICTURA Display Light 35-830/840/857-3800lm max.



Technical Details:

Luminous Flux:	3800 lm
LED Output:	34 W
Light Yield:	109 lm/W
Light Temperature:	3000, 4000, 5700 K
Light Color:	dualwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<5
Beam Angle:	110 °
Light Emission:	
LED-Chip Manufacturer:	Lumileds
LED-Chip:	SMD 3030
Number of LED:	80
Ignition Time:	<0,5 s
Input Current:	AC 100-240V, 50/60Hz
Power Consumption:	35 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	plug connector
Output of Driver:	DC 48-58V, 600mA
CC/CV:	CC
Input Lamp:	cable with plug
Switching Cycles:	>100.000
Ambient Temperature (TA):	-10°C - 40°C
Storage Temperature:	-40°C - 60°C

Dimensions:	525x163x39 mm
Mounting:	Wand
Montageart:	surface mounted
Pivot Range tilt:	80 °
IP Class:	20
Housing Color	silver
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	Displayleuchte
Cover:	clear
Net Weight:	950 g
Type of Packaging:	box
Weight incl. Packaging:	1.2 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,LM80
Messe-/Displayleuchte	
für Werbebanner oder Verkaufsregale	
for banners or shelves	
Lichtfarbe einstellbar: 3000K, 4000K, 5700K	
Kopf schwenkbar max. 10 Leuchten über ein Kabel	

Information and Downloads:

