



# Lucello Multi-CCT BL-Panel 6262-40-830/840-5000LM BAP UGR<19



## Technical Details:

|                              |                              |
|------------------------------|------------------------------|
| Luminous Flux:               | 5000 lm                      |
| Light Yield:                 | 125 lm/W                     |
| Light Temperature:           | 3000,3500,4000 K             |
| Light Color:                 | CCT Select                   |
| Color Rendering Index:       | ≥80 Ra                       |
| Color Consistency (SDCM):    | <4                           |
| Beam Angle:                  | 90 °                         |
| Unified Glare Rating (UGR):  | <19                          |
| Light Emission:              | downward                     |
| LED-Chip:                    | SMD                          |
| Ignition Time:               | <0,5 s                       |
| Input Current:               | AC 220-240V, 50/60Hz         |
| Power Consumption:           | Power Select (28,32,36,40 W) |
| Driver Manufacturer:         | Litegear                     |
| Power Factor (PF):           | >0.9                         |
| Input Driver:                | cable with flying leads      |
| Output of Driver:            | DC 32-42V, 700-1000mA        |
| CC/CV:                       | CC                           |
| Input Lamp:                  | plug connector               |
| Switching Cycles:            | >50.000                      |
| Electrical Protection Class: | II                           |
| Ambient Temperature (TA):    | -10°C - 40°C                 |
| Storage Temperature:         | -20°C - 60°C                 |

|   |                   |
|---|-------------------|
| Dimensions:                                       | 620x620x35 mm     |
| Mounting:   | Decke             |
| Montageart:                                       | recessed          |
| IP Class:   | 30 (44 room side) |
| IK Code:  | 02                |
| Housing Color                                     | white             |
| Housing Material:                                 | steel             |
| Coating:  | powder-coated     |
| Cover:  | prismatic         |
| Net Weight:                                       | 1960 g            |
| Type of Packaging:                                | box               |
| Dimensions of Packaging:                          | 643x665x45        |
| Weight incl. Packaging:                           | 2.6 kg            |
| Content Master Package:                           | 5                 |
| Dimensions of Master Package:                     | 650x686x255 mm    |
| Weight Master Package:                            | 12,85 kg          |
| Product Line:                                     | Advance Line      |
| Warranty  | 5 years           |
| Operating Hours:                                  | 50.000 h L80/B20  |
| Disposal Obligation:                              | ✓                 |
| Customs Tariff Number:                            | 9405499090        |
| Certifications                                    | CE,D              |
| Barcode:  | 4250557823522     |
| Bildschirmarbeitsplatz tauglich nach EN 12464-1   |                   |
| CCT-Select: schaltbare Lichtfarbe 3000,3500,4000K |                   |
| Power Select: 28, 32, 36, 40W Treiber einstellbar |                   |
| Backlite Technology                               |                   |
| OneFitAll   |                   |

Information and Downloads:

