

CONLUX Floodlight ASY60x15-1500-740-228000LM Dali Dim



Product information "CONLUX Floodlight ASY60x15-1500-740-228000LM Dali Dim"

LED Flood Light

Litegear® CONLUX is a stylish and modular LED outdoor floodlight. Available with different beam angles and power classes. Due to the use of a light weight aluminum housing, inox screws and strong bracket it has an excellent corrosion resistance. Conlux is the perfect solution for use in factories, sport fields, harbours, airports or for architectural applications. Because of its weather sealed standard you can use it permanently outside in rough environment conditions. We use very efficient LED chips. SMD chips have an optimized heat dissipation to guarantee a long lifespan. Dimming function on option (Dali dimming). Very light weight total 28,2kg
Dali dimmable Version
20kV surge protection device
Only 3-core cable needed

Applications:

- sport field: Soccer, Tennis, Basketball, Golf
- harbour, airport, warehouse
- industrial and architectural applications

Technical Details:

- Safety Tests: EN 60598-1:2015, EN 60598-2-5:1998, ZEK01.4-08, EN 62493:2010, IEC 60598-2-5: 1998, IEC 60598-1:2008, AS/NZS 60598:2.5:2002, AS/NZS 60598.1:2013
- EMC Test: EN 55015:2013, EN 61547:2009, EN 61000-3-2:2006+A1: 2009+A2:2009, EN61000-3-3:2013

Photobiological Safety: EN62471: 2008

Technical Details:

Luminous Flux	228000 lm
Light Yield:	152 lm/W
Light Temperature:	4000 K
Color Rendering Index (CRI)	≥70 Ra
Color Consistency (SDCM):	3
Power Consumption:	1500 W
Power Factor (PF):	0.95
Operating Hours:	>104.000 h L90B50
Switching Cycles:	>250.000
Ignition Time:	<0,5 s
Ambient Temperature (TA):	-20°C - 50°C
Housing Material:	aluminum
Housing Color	black
Coating:	powder-coated
Dimensions	888x588x457 mm
Net Weight:	28200 g
Warranty	5 years

Information and Downloads:

