

RETROVA SELECT 600 12/20-CCT-Select-1500-2600LM



Technical Details:

Luminous Flux:	2600 lm
LED Output:	19 W
Light Yield:	130 lm/W
Light Temperature:	3000,4000,5000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	120 °
Unified Glare Rating (UGR):	<24
Light Emission:	downward
LED-Chip Manufacturer:	Osram Opto Semiconductors
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 198 - 264V, 50/60Hz, DC 176 - 276V
Power Consumption:	Power Select (12, 14, 17, 20 W)
Contains Driver:	✓
Driver Manufacturer:	Osram
Power Factor (PF):	>0.95
Input Driver:	terminal
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-20°C - 55°C

Dimensions:	590x96x74 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	66
IK Code:	08
Housing Color	lichtgrey
Housing Material:	ABS
Special Feature of Housing:	schlagzäh
Cover:	prismatic
Net Weight:	903 g
Dimensions of Packaging:	620x100x82
Weight incl. Packaging:	0.999 kg
Content Master Package:	20
Dimensions of Master Package:	630x430x220 mm
Weight Master Package:	21,28 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405114090
Certifications	CE,D
Barcode:	4250557823812
Osram LED Treiber mit einstellbarem Ausgangsstrom:	
Leistung einstellbar: 12,14,17,20W max. 132lm/W	
EVG: ENEC-10/VDE/EMC/EL/CE; geeignet für Notstrom	
Anzahl pro Automat: 10A: 36, 16A: 50 Stück	
CCT Select: 3000K, 4000K, 5000K by switch	

