

Estella MKII 80-840-6800LM Dim Sensor



Technical Details:

Luminous Flux:	6800 lm
LED Output:	80 W
Light Yield:	85 lm/W
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<5
Beam Angle:	110x83 °
Unified Glare Rating (UGR):	<19
Light Emission:	
Dimmable:	✓
Method of Dimming:	Push-Dim
LED-Chip:	SMD 2835
Number of LED:	288
Ignition Time:	<0,5 s
Input Current:	AC 100- 277V, 50/60Hz
Power Consumption:	80 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	cable with plug
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	610x310x1950 mm
Mounting:	ground
IP Class:	40
Housing Color	silver
Housing Color (RAL Code):	similar 9006
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	Steel base
Cover:	prismatic
Net Weight:	14300 g
Type of Packaging:	box
Weight incl. Packaging:	16.2 kg
Content Master Package:	1
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE,EMC,LVD
Barcode:	4250557814025
LSS: B10 18 Leuchten, B16: 20 Leuchten	

Information and Downloads:

