

Order number: LG14750END

LANEA Office Lichtliniensystem 1500-35-840-100/45DA-W 5250lm (2500+2750lm)



Technical Details:

Luminous Flux:	5250 lm
LED Output:	35 W
Light Yield:	150 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Unified Glare Rating (UGR):	<19
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 50/60Hz
Power Consumption:	35 W
Contains Driver:	✓
Driver Manufacturer:	Litegear
Input Driver:	plug connector
Output of Driver:	DC 38V
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	plug connector
Switching Cycles:	>200.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-10°C - 40°C
Storage Temperature:	-20°C - 55°C

Dimensions:	1500x60x100 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	modular
Cover:	prismatic
Type of Packaging:	box
Weight incl. Packaging:	4.1 kg
Content Master Package:	5
Dimensions of Master Package:	1710x440x160 mm
Weight Master Package:	23,3 kg
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	50.000 h L90/B10
Disposal Obligation:	✓
Customs Tariff Number:	94051190
Certifications	CE,D
Barcode:	4250557822839
Elegante, modulare Lichtlinienleuchte für Büros	
Direkt/indirekt strahlend 19W + 16W (45°+100°)	
optional in Dualwhite lieferbar, Power Select	
Für Bildschirmarbeitsplätze geeignet UGR<19	
inkl. 7-adrigem Tragschienenprofil, Dali DT6	

Information and Downloads:

