


# Citana XL 25-CCT-2450LM Triac Dim 244 mm Ø



## Technical Details:

|                              |                             |
|------------------------------|-----------------------------|
| Luminous Flux:               | 2450 lm                     |
| LED Output:                  | 25 W                        |
| Light Yield:                 | 98 lm/W                     |
| Light Temperature:           | 3000,4000,6000 K            |
| Light Color:                 | CCT Select                  |
| Color Rendering Index:       | ≥80 Ra                      |
| Color Consistency (SDCM):    | <6                          |
| Beam Angle:                  | 110 °                       |
| Light Emission:              | downward                    |
| Dimmable:                    | ✓                           |
| Method of Dimming:           | "Triac Phasenan-/abschnitt" |
| LED-Chip:                    | SMD 2835                    |
| Ignition Time:               | <0,5 s                      |
| Power Consumption:           | 25 W                        |
| Contains Driver:             | ✓                           |
| Power Factor (PF):           | >0.9                        |
| CC/CV:                       | CC                          |
| Input Lamp:                  | terminal                    |
| Switching Cycles:            | >30.000                     |
| Electrical Protection Class: | II                          |
| Ambient Temperature (TA):    | -10°C - 40°C                |
| Storage Temperature:         | -10°C - 50°C                |

|   |                  |
|---|------------------|
| Dimensions:                                   | 244x85 mm        |
| Cut-Out Dimensions:                           | 195-210 mm       |
| Mounting:                                     | Decke            |
| Montageart:                                   | recessed         |
| IP Class:                                     | 20               |
| Housing Color                                 | white            |
| Housing Material:                             | Thermoplastic    |
| Special Feature of Housing:                   | IP 44 room side  |
| Cover:  | frosted          |
| Net Weight:                                   | 483 g            |
| Type of Packaging:                            | box              |
| Dimensions of Packaging:                      | 245x245x95       |
| Weight incl. Packaging:                       | 0.651 kg         |
| Content Master Package:                       | 20               |
| Dimensions of Master Package:                 | 525x525x510 mm   |
| Weight Master Package:                        | 14,27 kg         |
| Product Line:                                 | ECO Line         |
| Warranty                                      | 3 years          |
| Operating Hours:                              | 40.000 h L70/B30 |
| Disposal Obligation:                          | ✓                |
| Customs Tariff Number:                        | 9405409990       |
| Certifications                                | CE               |
| Barcode:                                      | 4250557818429    |
| CCT Select: Farbwahl 3000K, 4000K, 6000K      |                  |
| inkl. Metallring (chrome dunkel)              |                  |
| integrierter Treiber Anschlussklemme          |                  |
| dimmbar mediums Phasenan- / -abschnitt Dimmer |                  |

Information and Downloads:

