


Fenestra Circle Advance 240 18-827-1365LM



Technical Details:

Luminous Flux:	1365 lm
LED Output:	17 W
Light Yield:	76 lm/W
Light Temperature:	2700 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	110 °
Unified Glare Rating (UGR):	<24
Light Emission:	downward
LED-Chip Manufacturer:	Refond
LED-Chip:	SMD 2835
Number of LED:	90
Ignition Time:	<0,5 s
Input Current:	AC 200 - 240V, 50/60Hz
Power Consumption:	18 W
Contains Driver:	✓
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 25-40V, 450mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-40°C - 60°C

Dimensions:	238x13 mm
Installation Depth:	18 mm
Cut-Out Dimensions:	222-225 mm
Mounting:	ceiling,wall
Montageart:	recessed
IP Class:	20 (43 room side)
IK Code:	04
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Special Feature of Housing:	IP43 raumseits sonst IP20
Net Weight:	595 g
Type of Packaging:	box
Weight incl. Packaging:	0.693 kg
Content Master Package:	20
Dimensions of Master Package:	470x270x520 mm
Weight Master Package:	14,61 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	35.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,SELV,D
Barcode:	4250557820484

Information and Downloads:

