

Fina Circle 120 8-840-700LM



Technical Details:

Luminous Flux:	700 lm
LED Output:	8 W
Light Yield:	88 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	120 °
Light Emission:	downward
Ignition Time:	<0,5 s
Input Current:	AC 100 - 240V, 180mA, 50/60Hz
Power Consumption:	8 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	cable with flying leads
Output of Driver:	DC 27-42V, 280mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>25.000
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	120x22 mm
Installation Depth:	22 mm
Cut-Out Dimensions:	100 mm
Mounting:	Decke
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Cover:	opal
Net Weight:	180 g
Type of Packaging:	box
Dimensions of Packaging:	170x45x175
Weight incl. Packaging:	0.233 kg
Content Master Package:	40
Dimensions of Master Package:	490 x360 x 370 mm
Weight Master Package:	10 kg
Product Line:	ECO Line
Warranty	2 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557808277

Information and Downloads:

