


Acria 24-830-860-2400LM IP54 - OneFitAll



Technical Details:

Luminous Flux:	2400 lm
LED Output:	23 W
Light Yield:	100 lm/W
Light Temperature:	3000,4000,6000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 2835
Number of LED:	162
Ignition Time:	<0,5 s
Input Current:	AC 165-265V, 50/60Hz
Power Consumption:	Power Select (15,18, 24 W)
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 70-85V, 275-300mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Kabel mit Klemmen
Switching Cycles:	>25.000
Electrical Protection Class:	II
Loop-Through Cabling:	✓
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-20°C - 50°C

Dimensions:	285x285x58 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	54 (54 room side)
IK Code:	08
Housing Color	white
Housing Material:	Polycarbonat/Alu
Special Feature of Housing:	schnelle Montage
Cover:	opal
Net Weight:	990 g
Type of Packaging:	box
Dimensions of Packaging:	310x310x61
Weight incl. Packaging:	1.12 kg
Content Master Package:	10
Dimensions of Master Package:	615x 300x310 mm
Weight Master Package:	12,05 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	35.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,D
Barcode:	4250557821405
Über Schalter wählbare Lichtfarbe 3000,4000,6500K	
IP54 bei Deckenmontage, nicht bei Wandmontage!	
zweigeteiltes Gehäuse, leichte Montage	
Leistung schaltbar: 15, 18, 24W: 1500-2400lm	
Klemmterminal zum Durchschleifen von 230V	

Information and Downloads:

