


Newtura Round 500 42-840-4260LM



Technical Details:

Luminous Flux:	4260 lm
LED Output:	37 W
Light Yield:	109 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥84 Ra
Color Consistency (SDCM):	<4
Beam Angle:	110 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	Samsung
LED-Chip:	SMD 2835
Number of LED:	182
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	39 W
Contains Driver:	✓
Driver Manufacturer:	Kegu
Power Factor (PF):	>0.96
Input Driver:	terminal
Output of Driver:	DC 33-46V, 900mA
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	500x50 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	20 (54 room side)
IK Code:	08
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Cover:	opal
Net Weight:	4800 g
Type of Packaging:	box
Dimensions of Packaging:	550x550x90
Weight incl. Packaging:	6.2 kg
Content Master Package:	2
Dimensions of Master Package:	555x195x570 mm
Weight Master Package:	13,0 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE,LM80,SELV
Barcode:	4250557810263
opt. Ausgangsleistung einstellbar: 28, 32, 36, 42W	
opt. Adjustable DC output current: 28, 32, 36, 42W	
integr. Motionssensor: optional/ on demand	
Dali Driver: optional/ on demand	
Fangseil und Drehverschluß	

Information and Downloads:

