


Cappila XTreme MKIII 1500 60-860-8700lm



Technical Details:

| | |
|------------------------------------|------------------------|
| Luminous Flux: | 8700 lm |
| Light Yield: | 145 lm/W |
| Light Temperature: | 6000 K |
| Light Color: | cold white |
| Color Rendering Index: | ≥80 Ra |
| Color Consistency (SDCM): | <4 |
| Beam Angle: | 240 ° |
| Unified Glare Rating (UGR): | <25 |
| Light Emission: | downward |
| LED-Chip Manufacturer: | San'an |
| LED-Chip: | SMD 2835 |
| Ignition Time: | <0,5 s |
| Input Current: | AC 220 - 240V, 50/60Hz |
| Power Consumption: | 60 W |
| Contains Driver: | ✓ |
| Driver Manufacturer: | Tridonic |
| Power Factor (PF): | >0.92 |
| Input Driver: | terminal |
| CC/CV: | CC |
| Input Lamp: | Terminal |
| Switching Cycles: | >100.000 |
| Electrical Protection Class: | I |
| Compatible with Emergency Current: | ✓ |
| Loop-Through Cabling: | ✓ |
| Ambient Temperature (TA): | -20°C - 45°C |
| Storage Temperature: | -20°C - 60°C |

| | |
|-------------------------------|------------------|
| Dimensions: | 70x1490 mm |
| Mounting: | ceiling,wall |
| Montageart: | surface mounted |
| IP Class: | 69 |
| IK Code: | 10 |
| Housing Color | white/Chrom |
| Housing Material: | Polycarbonat |
| Special Feature of Housing: | Tube |
| Cover: | opal |
| Net Weight: | 1807 g |
| Type of Packaging: | box |
| Dimensions of Packaging: | 1580x90x90 |
| Weight incl. Packaging: | 2.1 kg |
| Content Master Package: | 10 |
| Dimensions of Master Package: | 1615x435x200 mm |
| Weight Master Package: | 21,85 kg |
| Product Line: | Premio Line |
| Warranty | 5 years |
| Operating Hours: | 50.000 h L80/B10 |
| Disposal Obligation: | ✓ |
| Customs Tariff Number: | 9405114090 |
| Certifications | CE,LM80,D |
| Barcode: | 4250557821214 |

Information and Downloads:

