

Catena FlexStrip Advance CV 120R, 9,6W/m



Technical Details:

Luminous Flux per Meter:	960 lm
Output per Meter:	9.6 W
Luminous Flux:	4000 lm
Light Yield:	100 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥90 Ra
Color Consistency (SDCM):	<3
Beam Angle:	120 °
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 3528
LED per Meter:	120
Cut After:	50 mm
Ignition Time:	<1 s
Input Current:	DC 24V
Power Consumption:	48 W
Output of Driver:	DC 24V
CC/CV:	CV
Input Lamp:	cable with flying leads
Input Strip:	Kabel mit offenen Enden - both sides
Ambient Temperature (TA):	-20°C - 55°C
Storage Temperature:	-40°C - 60°C

Dimensions:	5000x8x2,5 mm
IP Class:	20
Net Weight:	72 g
Type of Packaging:	bag
Dimensions of Packaging:	215x240x5
Weight incl. Packaging:	0.123 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	8539510000
Certifications	CE
Barcode:	4250557820699
maximaler Biegeradius: 50mm	
max. bending radius: 50mm	

Information and Downloads:

