

Velostra Line 1500 30-840-4200LM



Technical Details:

Luminous Flux:	4200 lm
LED Output:	29 W
Light Yield:	140 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	120 °
Unified Glare Rating (UGR):	<24
Light Emission:	downward
LED-Chip Manufacturer:	Bridgelux
LED-Chip:	SMD 2835
Number of LED:	288
Ignition Time:	<0,5 s
Input Current:	AC 200 - 240V, 280mA, 50/60Hz
Power Consumption:	30 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	cable with plug
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-10°C - 40°C
Storage Temperature:	-20°C - 55°C

Dimensions:	1498x46x65,5 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20
IK Code:	08
Housing Color	Alu
Housing Material:	aluminum
Special Feature of Housing:	PC Cover
Cover:	opal
Net Weight:	820 g
Type of Packaging:	bag
Weight incl. Packaging:	0.88 kg
Content Master Package:	6
Dimensions of Master Package:	1640x188x120 mm
Weight Master Package:	5,770 kg
Product Line:	ECO Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	94054239
Certifications	CE,TÜV,LM80
Barcode:	4250557822624
Einfache, und schnelle Montage	
LED-Modul für Tragschiene	

Information and Downloads:



