

Xona Maxima Basic Unit 150DAS 50-860-7380LM



Technical Details:

| | |
|------------------------------|---|
| Luminous Flux: | 7380 lm |
| LED Output: | 48 W |
| Light Yield: | 211 lm/W |
| Light Temperature: | 6000 K |
| Light Color: | cold white |
| Color Rendering Index: | ≥80 Ra |
| Color Consistency (SDCM): | <4 |
| Unified Glare Rating (UGR): | <22 |
| Light Emission: | downward |
| LED-Chip Manufacturer: | Epistar |
| LED-Chip: | SMD 2835 |
| Ignition Time: | <0,5 s |
| Input Current: | AC 170 - 264V, 330mA, 50/60Hz, DC 170-230V |
| Power Consumption: | 35 W |
| Contains Driver: | ✓ |
| Driver Manufacturer: | Litegear |
| Power Factor (PF): | >0.95 |
| Input Driver: | terminal |
| Output of Driver: | DC 55-80V, 620mA |
| CC/CV: | CC |
| Input Lamp: | plug connector |
| Switching Cycles: | >100.000 |
| Electrical Protection Class: | I |
| Ambient Temperature (TA): | -20°C - 50°C |

| | |
|-------------------------------|-------------------|
| Dimensions: | 1498,5x70x39,4 mm |
| Mounting: | Decke |
| Montageart: | surface mounted |
| IP Class: | 30 |
| IK Code: | 02 |
| Housing Color | white |
| Housing Material: | steel |
| Coating: | lacquered |
| Cover: | clear |
| Net Weight: | 1670 g |
| Type of Packaging: | box |
| Weight incl. Packaging: | 1.85 kg |
| Content Master Package: | 10 |
| Dimensions of Master Package: | 1550x390x210 mm |
| Weight Master Package: | 19,8 kg |
| Product Line: | Advance Line |
| Warranty | 5 years |
| Operating Hours: | 50.000 h L70/B20 |
| Disposal Obligation: | ✓ |
| Customs Tariff Number: | 9405409990 |
| Certifications | CE,TÜV,ENEC,LM80 |
| Barcode: | 4250557815220 |

Information and Downloads:



