



Campa Flex SF Floodlight ASY80x30-680-757-94000LM



Technical Details:

Luminous Flux:	93600 lm
LED Output:	650 W
Light Yield:	138 lm/W
Light Temperature:	5700 K
Light Color:	daylight
Color Rendering Index:	≥70 Ra
Color Consistency (SDCM):	<3
Beam Angle:	80x30 °
Light Emission:	downward
LED-Chip Manufacturer:	Seoul Semiconductor
LED-Chip:	SMD 3535
Ignition Time:	<0,5 s
Input Current:	AC 100 - 265V, 50/60Hz
Power Consumption:	680 W
Contains Driver:	✓
Driver Manufacturer:	Meanwell
Power Factor (PF):	>0.95
Input Driver:	cable with flying leads
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 55°C

Dimensions:	890x390x240 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	66
IK Code:	10
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	modular, swivelling
Cover:	Lens
Net Weight:	22500 g
Type of Packaging:	box
Content Master Package:	1
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	97.000 h L80/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE,ENEC,LM80,D
Barcode:	4250557821092
optional Dali / 0-10V dimmbar	
Akzo Nobel Beschichtung	
10KV surge predetection	

Information and Downloads:



