


Campa Flex Floodlight SP300-840-36800LM



Technical Details:

Luminous Flux:	36800 lm
LED Output:	280 W
Light Yield:	123 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	25 °
Unified Glare Rating (UGR):	<19
Light Emission:	
LED-Chip Manufacturer:	Lumileds
LED-Chip:	SMD 5050
Ignition Time:	<0,5 s
Input Current:	AC 100 - 265V, 50/60Hz
Power Consumption:	300 W
Contains Driver:	✓
Driver Manufacturer:	Meanwell
Power Factor (PF):	>0.95
Input Driver:	cable with flying leads
CC/CV:	CC
Input Lamp:	cable with flying leads
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 55°C

Dimensions:	275x320x433 mm
Mounting:	ceiling,wall,ground
Montageart:	surface mounted
Pivot Range tilt:	60 °
IP Class:	66
IK Code:	10
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	modular, swivelling
Cover:	frosted
Net Weight:	8380 g
Type of Packaging:	box
Weight incl. Packaging:	9.202 kg
Content Master Package:	2
Dimensions of Master Package:	765 x 49x 235 mm
Weight Master Package:	16 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	100.000 h L80/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,ENEC,LM80
Barcode:	4250557813417
Meanwell® HLG-C Driver	
Akzo Nobel Beschichtung/Coating	

Information and Downloads:

