


Luna Plane IP66 Floodlight 13-840-1250LM



Technical Details:

Luminous Flux:	1250 lm
LED Output:	13 W
Light Yield:	96 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
LED-Chip Manufacturer:	Seoul Semiconductor
LED-Chip:	SMD 2835
Ignition Time:	<1 s
Input Current:	AC 85 - 265V, 50/60Hz
Power Consumption:	13 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	cable with plug
Output of Driver:	DC 36 - 42V, 300mA
CC/CV:	CC
Input Lamp:	cable with plug
Switching Cycles:	>50.000
Ambient Temperature (TA):	-20°C - 50°C
Storage Temperature:	-40°C - 60°C

Dimensions:	175x135x42 mm
Mounting:	ceiling,wall,ground
Montageart:	surface mounted
IP Class:	66
IK Code:	08
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Cover:	prismatic
Net Weight:	1030 g
Type of Packaging:	box
Dimensions of Packaging:	190x235x75
Weight incl. Packaging:	1.155 kg
Content Master Package:	12
Dimensions of Master Package:	500x390x260 mm
Weight Master Package:	13,5 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE,GS
Barcode:	4250557820460

Information and Downloads:

