


Cetara Office 6262-36-840-3125-4850LM



Technical Details:

Luminous Flux:	4400 lm
LED Output:	35 W
Light Yield:	122 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	120 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
LED-Chip Manufacturer:	Everlight
LED-Chip:	SMD 4014
Ignition Time:	<0,5 s
Power Consumption:	36 W
Output of Driver:	DC 32-42V, 500-1000mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Ambient Temperature (TA):	-10°C - 40°C

Dimensions:	620x620x10 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20 (44 room side)
IK Code:	02
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Cover:	opal
Net Weight:	2330 g
Type of Packaging:	box
Dimensions of Packaging:	650x665x35
Weight incl. Packaging:	2.8 kg
Content Master Package:	5
Dimensions of Master Package:	657x203x688 mm
Weight Master Package:	14,82 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,D
Barcode:	4250557812625
ohne LED-Treiber	
without LED driver	
Achtung EU-Größe nicht für deutsche Decken	
EU size can not be used for German ceilings	

Information and Downloads:

