


# Fenestra Value Square MKIII 6262 36-940-3960lm IP66 UGR<21, 110lm/W, RAL9003



## Technical Details:

Luminous Flux:	3960 lm
LED Output:	35 W
Light Yield:	113 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥90 Ra
Color Consistency (SDCM):	<4
Beam Angle:	110 °
Unified Glare Rating (UGR):	<21
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Power Consumption:	35 W
Contains Driver:	✓
Power Factor (PF):	>0.96
Output of Driver:	DC 32-42V, 500-1000mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 60°C

Dimensions:	620x620x12 mm
Mounting:	Decke
IP Class:	66
IK Code:	06
Housing Color	white
Housing Color (RAL Code):	similar 9003
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	weather proof
Cover:	opal
Net Weight:	3166 g
Type of Packaging:	box
Dimensions of Packaging:	645x645x45
Weight incl. Packaging:	3.65 kg
Content Master Package:	4
Dimensions of Master Package:	650 x 650 x240 mm
Weight Master Package:	19,4 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,LM80,D
Barcode:	4250557823171
inkl. Klemmdose mit Terminalblock in/out	
Brandschutzklasse UL94-HB	
auch mit dimmbarem Treiber lieferbar	

### Information and Downloads:

