


Placida Circle 220 18-830-1420LM



Technical Details:

Luminous Flux:	1420 lm
LED Output:	18 W
Light Yield:	84 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Light Emission:	downward
LED-Chip Manufacturer:	Epistar
LED-Chip:	SMD 4014
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	17 W
Contains Driver:	✓
Power Factor (PF):	>0.55
Input Driver:	cable with flying leads
Output of Driver:	DC 81V, 200mA
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>30.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	220x18 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	20
Housing Color	white
Housing Material:	plastic
Special Feature of Housing:	flat only 18mm high
Cover:	opal
Net Weight:	367 g
Type of Packaging:	box
Weight incl. Packaging:	0.47 kg
Content Master Package:	20
Dimensions of Master Package:	472x295x285 mm
Weight Master Package:	14,5 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	30.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE
Barcode:	4250557808994

Information and Downloads:

